

KARTA KATALOGOWA

Wiertło udarowe z chwytem SDS-Plus



System szybkiego mocowania SDS-Plus: 2 rowki wzdłużne i 2 okrągłe przy końcu części mocowanej.
Możliwość stosowania do wiertarek różnych producentów

Art nr	M	Dc	Phi	Dk	Zestaw	Sl	kg	Oj	Zl	
230395		460	20			400	0,585	1	184.95	
230396		600	20			540	0,737	1	228.38	
230397		460	22			400	0,669	1	268.74	
230398		460	25			400	0,998	1	311.90	
230430		110	5			50	0,037	1	20.21	
230431		160	5			100	0,042	1	23.18	
230432		110	5,5			50	0,037	1	19.31	
230433		160	5,5			100	0,045	1	24.98	
230434		110	6			50	0,039	1	19.98	
230436		160	6			100	0,045	1	21.87	
230438		110	6,5			50	0,038	1	25.02	
230438/		160	7			100	0,050	1	30.60	
A										
230438/		160	6,5			100	0,047	1	29.52	
B										
230440		110	7			50	0,041	1	27.81	
230442		110	8			50	0,046	1	25.79	
230442/		160	8			100	0,056	1	26.10	
A										
230444		210	8			150	0,064	1	32.31	
A										
230444/		460	8			400	0,150	1	88.70	
A										
230448		160	10			100	0,065	1	31.91	
230450		210	10			150	0,087	1	41.63	
230450/		260	10			150	0,118	1	47.70	
A										
230451		460	10			400	0,192	1	91.31	
230453		210	12			150	0,107	1	42.17	
230454		160	12			100	0,097	1	35.87	

Art nr	M	Dc	Phi	Dk	Zestaw	Sl	kg	Oj	Zl
--------	---	----	-----	----	--------	----	----	----	----

230456		260	12			200	0,159	1	56.25	
230457		460	12			400	0,263	1	91.85	
230458		160	13			85	0,111	1	60.53	
230459		600	12			540	0,286	1	133.70	
230460		160	14			100	0,087	1	52.02	
230460/ A		260	14			200	0,180	1	63.23	
230461		460	14			400	0,257	1	97.38	
230464		210	16			150	0,197	1	73.62	
230466		460	16			400	0,418	1	133.56	
230467		600	14			540	0,339	1	141.57	
230473		600	16			540	0,561	1	152.69	
230474		210	20			150	0,246	1	140.13	
230475		460	18			400	0,475	1	152.87	
230478/ 1		600	10			540	0,270	1	119.43	